Index

Symbols

(θ, γ)-Executability, **146**
$B^+_{as}(r)$, 160, 175
$B^+_{cc}(r)$, 175, 234
$B^+_{other}(r)$, 234
$B^-_{as}(r)$, 184, 186
$B^-_{cc}(r)$, 234
$B^-_{other}(r)$, 234
$B_{cc}(r)$, 160
F-concurrent, **150**, 151, 154, 156
F-preference, 192
S-concurrent, 150, **150**, 151
$\Gamma^{[]}(\mathfrak{a})$, **229**
$\Pi^{\text{action}}_{\mathfrak{b}}(\mathcal{BS})$, **227**
$\neg.B^-(r)$, 160
$\neg.B^-_{as}(r)$, 175
$\neg.B^-_{cc}(r)$, 175
$\models_{\mathcal{B}Sem^{\mathfrak{a}}_{\mathfrak{h}}}$, **222**
d_{G}, **60**
ACT(γ), **221**
ACT(Φ), **220**
App$_{\mathcal{BP},\mathcal{O}}(\mathcal{BS})$, **234**
BBT$^{\mathbf{a}}$, **216**
$\mathcal{B}At_1(\mathfrak{a}, \mathfrak{b})$, **213**
$\mathcal{B}At_i(\mathfrak{a}, \mathfrak{b})$, 214
$\mathcal{B}_{\mathfrak{a}}(\mathfrak{b}, \chi)$, **213**
$\mathcal{B}Cond^{\mathfrak{a}}(\mathfrak{h})$, **223**
$\mathcal{BL}^{\mathfrak{a}}_i$, **214**
$\mathcal{BL}^{\mathfrak{a}}_\infty$, 244
$\mathcal{B}Lit_i(\mathfrak{a}, \mathfrak{b})$, **214**
$\mathcal{B}Lit_\infty(\mathfrak{a}, \mathfrak{b})$, **215**
$\mathcal{B}Lit_\infty(\mathfrak{a}, \mathrm{A})$, 225
BSemT$^{\mathbf{a}}$, **217**
$\mathcal{B}Sem^{\mathfrak{a}}_{\mathfrak{h}}$, **217**, **220**
$\mathcal{B}Sem^{\mathtt{heli2}}_{\mathtt{tank2}}$, 218
$\mathcal{B}Sem^{\mathtt{tank1}}_{\mathtt{heli1}}$, 218
BT$^{\mathbf{a}}$, **221**
CCC(γ) **,** 221
CCC(Φ), **220**
$\mathfrak{a}: bel_ccc_act(\sigma)$, 243
$[\rho]$, **227**
[], **227**
$\flat$, **463**
cd$(\cdot, \cdot)$, **58**
EXPSPACE, **401**
EXPTIME, **401**
NPMV^{NP}, **406**
NPMV, **406**
PSPACE, 402–404
$\otimes_{ig}$, **303**
$\otimes_{in}$, **303**
$\otimes_{nc}$, **303**
$\otimes_{pg}$, **303**
$\mathcal{AB}$, **146**
$\mathcal{AC}$, **158**
$\mathcal{AS}$, 147, 148, 150–152, 154–156, 160
$\mathcal{BS}$, **226**
$\mathcal{BP}$, **225**
$\mathcal{C}$, **76**
$\mathcal{F}$, **76**
$\mathcal{S}$, **76**
$\mathcal{T}$, **76**
conc, **147**, 156, 168
Sem$_{feas}$, 219
Sem$_{rat}$, 219
Sem$_{reas}$, 219
Σ-node, 41
App$_{\mathcal{PP},\mathcal{O}_{\mathcal{S}}}(\mathcal{P}S)$, **308**
App$_{\mathcal{P},\mathcal{O}_{\mathcal{S}}}(S)$, 174
$\mathbf{A}_{\mathcal{P},\mathcal{O}_{\mathcal{S}}}(S)$, 190
TPA$_{\mathcal{P},\mathcal{O}_{\mathcal{S}}}$, 189
$\mathbf{T}_{\mathcal{P},\mathcal{O}_{\mathcal{S}}}$, 190, 191
$\mathbf{T}_{\mathcal{PP},\mathcal{O}_{\mathcal{S}}}$, **314, 315**
red$^{\mathcal{BS}}(\mathcal{BP}, \mathcal{O}_{\mathcal{S}})$, **242**
$\wp$
(as graph mapping), **41**
$\mathcal{S}^{\text{ext}}$, **230**, 242, 246, 247
GUI
Java, **117**
Tcl/Tk, **117**
ground_control, 334
IMPACT, 242
$\Pi^{\text{action}}_{\sigma}(\mathcal{BS})$, **227**
$\Pi^{\text{state}}_{\mathfrak{b}}(\mathcal{BS})$, **227**
$\Pi^{\text{state}}_{\sigma}(\mathcal{BS})$, **227**
Info$(\mathfrak{a})$, *see* $\Gamma^{[]}(\mathfrak{a})$ 229
map, **225**
mar, **225**
nt, 39
no_go, **9**
Nouns, 39, **39**
$\mathfrak{a}$_part(χ), **223**
$\mathfrak{h}$_part(χ), **223**
$\mathcal{SH}$, 42
BT$^{\mathfrak{a}}$: B-proj-select$(r, \mathfrak{h}, \phi)$, **222**
BT$^{\mathbf{a}}$: proj-select(agent, $=$, $\mathfrak{h}$), **221**
v: nt, **39**
implement_service, **99**
safe_ccc, **87**
FIPA, 3
InfoSleuth, 17
$\mathfrak{Trans}^{\text{action}}(\mathcal{BS}, \mathfrak{b})$, **245**
$\mathfrak{Trans}^{\text{action}}(\mathcal{BS})$, **244**
$\mathfrak{Trans}$, **244**
$\mathfrak{Trans}(\mathcal{BP})$, 245, 248, 249
$\mathfrak{Trans}^{\text{state}}(\mathcal{BS}, \mathfrak{b})$, **245**
v, 39

Verbs, 39, **39**
autoPilot, 145, 157, 163, 169, 170, 330, 334, 339, 340, 392
clock, 168, 170
credit, 141, 166, 169
gps, 145, 158, 165, 170
ground_control, 330, 332, 334, 335, 339, 344, 348, 349, 355, 356, 359, 363, 392
oracle, 345
plant, 162, 169, 195
profiling, 145, 158, 165, 169
radar, 344
saleNotification, 166, 170
salesMonitor, 168
satellite, 141
shipping, 162, 169
supplier, 144, 151, 157, 161, 162, 168, 176
terrain, 163, 169, 171, 209
truck, 141
CFIT, 145, 157, 163, 169, 170, 330, 332, 351
Info(·), **229**
CFIT*, 345
STORE, 145, 158, 165, 169
CHAIN, 144, 149, 151, 157, 161, 168, 175, 176, 178, 180, 184
3SAT, 402

A
$\mathbf{A}_{\mathcal{P},\mathcal{O}_{\mathcal{S}}}(S)$, 190
a_part(χ), **223**
$\mathcal{AB}$, **146**
$\mathcal{AC}$, **158**
ACCESS, 13, 36
ACT(γ), 221
ACT(Φ), **220**
action
delayed, 11, 14
strongly safe, **475**
action atom, *see* atom, action 143
action atoms
compatible, **213**
action base, *see* base, action 146
action closure, *see* closure, action 174
action code, **143**
action consistency, *see* consistency, action 173
for map, 231
of $\mathcal{PS}$, **309**
action constraint, *see* constraint, action 157
action constraint satisfaction, *see* satisfaction, action constraint 158
action events, 333
action execution, **147**
action policy, 32, 34, 35
action rule, 160, *see* rule, action 160
action secure distortion policy, *see* distortion, policy, action secure 344
action status atom, *see* atom, action status 160
actions, 33
ACYCLIC, **401**
Add, **143**
adminImpact, 117–119, **122**
agent, 29
airplane, 13
autoPilot, 8, 10, 11, 17, 19, 20, 22, 32–34, 145, 157, 163, 169, 170, 330, 334, 339, 340, 392
clock, **168**, 170
content determination, 6
coordination, **210**
credit, 5, 8, 31, 141, 166, 169, 329
enemy vehicle, **209**
gps, 9, 10, 17, 32, 63, 145, 158, 165, 170
ground_control, 330, 332, 334, 335, 339, 344, 348, 349, 355, 356, 359, 363, 392
helicopter, **210**
interface, 6
inventory, 12
location, 9, 11
locERCTotals, 519, 524, 525
locTotals, 519–521, 524
oracle, **345**
plant, 13, 14, 18, 21, 30, 36, 162, 169, 195
product database, 5
profiling, 5, 8, 17, 19, 31, 34, 46, 145, 158, 165, 169
radar, **344**
regular, **493**
saleNotification, 6, 166, 170
sales, 17
salesMonitor, **168**
satellite, 9, 32, 35, 57, 141
shipping, 13, 162, 169
supplier, 13, 14, 18, 22, 32, 36, 144, 151, 157, 161, 162, 168, 176
tank, 18
terrain, 9, 35, 40, 163, 169, 171, **209**
tracking, **210**
transportation, 14
truck, 13, 19, 141
weakly regular, 477
Agent-0, **204**
agent action security function, *see* function, agent action security 339
agent applications, 2
data integration agents, 1
mobile agents, 2
monitoring interestingness, 2
personalized visualization, 2
software interoperability agents, 2
agent approximation, *see* approximation, agent 358

agent approximation program, *see* approximation, agent, program 382
agent architecture, 19
  deliberative, 51
  hybrid, 51
  reactive, 51
agent consequence relation, *see* relation, agent consequence 335
agent decision cycle algorithm, **168**
agent decision making, *see* decision making, agent 17
agent program, 143, 161, 167, **171**, 172, 174, 177–185, 187–190, 193, 194, 197, 198, 202, 203, 205
  b-bounded, **492**
  b-regular, **492**
  deontically stratifiable, 474
  probabilistic, **304**
  regular, 186
  weak regular, **475**
agent secrets function, *see* function, agent secrets 339
agent state, 333, **334**, 368, 396
Agent-0, 19
agentize, 3, 21, 529
AgentTable, 45, 61, **122**
annihilator, 303
annotated ccc
  satisfaction of an, **307**
annotation item, *see* item, annotation 304
$\mathbf{App}_{\mathcal{P},\mathcal{O}_S}(S)$, 174
$\mathbf{App}_{\mathcal{BP},\mathcal{O}}(\mathcal{BS})$, **234**
apply, 97, 98
apply, **97**
approximate
  condition, **353**
  consequence relation, **356**, 357, 358, 372
  current history, *see* history, approximate current 351
  data security, 331, *see* security, data, approximate 359
  fact language, **352**, 372, 377
  facts, 372, 384
  history, *see* history, approximate 354
  language, 353, 356, 358
  secrets, **356**, 358, 372
  secrets, correctness, **356**
  security check, 331, **348**, 349, 359, 361, 365
  state, **354**, 355
  state function, 354, **354**, 361
approximation
  agent, **358**, 363, 372, 391
    program, 369, **382**, 384
    static, **364**
  compact, **361**, 362
  current history, 358
  history, 365, 373, 374
  possible history, **350**
  rule
    consequence, 372
    history, *see* history, approximation rule 372
    secrets, 372
    state, 372
$\mathcal{AS}$, 147, 148, 150–152, 154–156, 160
associativity, 303
atom
  action, 143, **143**, 160
  action status, 160, **160**, 171, 172, 174, 176, 181, 192
  code call, 160
attributes
  service description, 53
automaton
  finite state, 19

B
$\flat$, **463**
backtracking, 416
base
  action, **146**, 148, 154, 155, 159, 168, 172, 193, 195, 197, 202, 203
base language, 22
base types, **97**
$\mathbf{BBT^a}$, **216**
$\mathcal{B}Cond^{\mathfrak{a}}(\mathfrak{h})$, **223**
BDI, 17, 19
BDI-agents, **204**
$\mathcal{B}_{\mathfrak{a}}(\mathfrak{b}, \chi)$, **213**
$\mathbf{BT^a}$
  as distinguished datatype, 226
$\mathcal{B}At_1(\mathfrak{a}, \mathfrak{b})$, **213**
$\mathcal{B}At_i(\mathfrak{a}, \mathfrak{b})$, 214
$\mathcal{BL}_i^{\mathfrak{a}}$, **214**
$\mathcal{B}Lit_i(\mathfrak{a}, \mathfrak{b})$, **214**
$\mathcal{B}Lit_\infty(\mathfrak{a}, \mathfrak{b})$, **215**
belief
  atom, 212, **213**, 382
  languages
    of level 0, **214**
    of level 1, **214**
  literal, **213**
    nested, **214**
    of level 1, **213**
  semantics table, 212, **217**
  table, 212, **221**
    basic, 212, **216**
    compatibility, 247
belief data structures, 209
belief formulae
  general, **215**
belief semantics table
  probabilistic, **324**

belief status set
  action closed, **233**
  deontically closed, **232**
belief table
  probabilistic, **324**
belief-semantics table, 211
beliefs, 7, 8, 10, 11, 14, 32, 35
BSemT$^{\mathbf{a}}$
  as distinguished datatype, 226
binding pattern, **463**, 464–466
  ordering on, **464**
binding term, **463**
bistructure, 490, **490**
$\mathcal{BL}^{\mathfrak{a}}_{\infty}$, 244
bottomline, 303
$\mathcal{BP}$, **225**
  reduct of, **242**
BT$^{\mathfrak{a}}$: B-proj-select(r, $\mathfrak{h}$, ϕ), **222**
$\mathcal{BS}$, **226**
BSemT$^{\mathbf{a}}$, **217**
BSemT$^{\mathfrak{a}}$: select(agent, $=$, $\mathfrak{h}$)
  as distinguished datatype, 226
BT$^{\mathfrak{a}}$: B-proj-select(r, $\mathfrak{h}$, ϕ)
  as distinguished datatype, 226
BT$^{\mathbf{a}}$, **221**

C
$\mathcal{C}$, **76**
 conc, 147, 156, 168
Carnot, 105, 107
causal dependency, *see* dependency, causal 357
CCC(γ), 221
CCC(Φ), **220**
cd($\cdot$, $\cdot$), **58**
cf, 195, 196
CFT, **471**
C-hard, **402**
class, **117**
  hierClass, **117**
  tableClass, **117**
  thesClass, **117**
closure
  action, **174**, 175, 181, 200
    of $\mathcal{BS}$, **234**
    relatived, 189
    relativized, **188**
  deontic, **174**, 175, 181, 200
    of $\mathcal{BS}$, 233
CNF, **402**
coalition formation, 18
code call
  probabilistic, **297**
  software, 159
code call condition
  annotated, **304**
  compatible, **213**
  history, 374, 377, 382
code calls
  basic, 229
  extended, 209, **229**, 243
coherence
  local, *see* local coherence 236
COINS, 21, 74
COM, 115, 116
commutativity, 303
compact approximation, *see* approximation, compact 361
compact version, **362**
comparison constraint, *see* constraint, comparison 373
compatibility, 237
  with **BSemT$^{\mathbf{a}}$**, 231
  with **BT$^{\mathbf{a}}$**, 231
  wrt **BSemT$^{\mathbf{a}}$**, **238**
  wrt **BT$^{\mathbf{a}}$**, **237**
compatible history, *see* compatible, history 342
complete, **402**
completeness, **402**, **405**
complexity classes
  deterministic, **401**
component
  strongly connected, 494, **494**
ConGolog, **205**
concurrency
  notion of, **147**, 156, 168
  strongly safe, **477**
  weak, 156
concurrent execution, 142, 148
  full, **150**, 151, 156
  sequential, 150, **150**, 151
  weak, **148**, 149–151
condition
  belief, 222, *see* condition, belief 222, **223**, 231, 243
  history, *see* history, condition 370
condition correspondence relation, *see* relation, condition correspondence 353
conflict free, **469**
conflict freedom
  test, **470**
conflicting modalities, **467**
consequence approximation rule, *see* approximation, rule, consequence 372
consistency
  action, **173**, 175, 178
    for $\mathcal{BS}$, **231**
  deontic, **173**, 175, 177, 178
    for $\mathcal{BS}$, **231**
  state, 175

constraint
action, 143, **157**, 158, 159, 168, 171, 186, 197, 200, 203
comparison, **373**
history, 373, 375, 377, 382
integrity, 142, 147, 159, 168, 171, 175, 178, 179, 185, 190, 191, 202, 203
prerequisite-free, **487**
pure history, **373**, 374, 382
contract net, 18, 207, *see* net, contract 288
correct distortion, *see* distortion, correct 346
correct overestimations, *see* overestimations, correct 357
correct underestimation, *see* underestimation, correct 357
cost function, 195
weak/strong monotonic, 196

D
heterogeneous, 15
data complexity, 409
data security, *see* security, data 343
Datalog, 16
dbImpact, 117–119, **122**
db_create, 120, **128**
db_getAgentInfo, 121, **130**, 138, 139
db_getAgents, 121, **130**, 139
db_getAgentTypes, 121, **130**, 139
db_getServicesToDelete, 121, **131**
db_getServices, 121, **131**
db_init, 117, 120, 122, **128**, 137, 138
db_insertAgent, 121, **131**, 139
db_insertService, 122, **132**, 140
db_quit, 120, 122, **128**
db_removeAgent, 121, **132**
db_removeAllServices, 122, **133**
db_removeId, 122, **132**
db_removeService, 122, **132**
hier_create, 119, **123**
hier_emptyId, 119, **124**, 136
hier_firstId, 119, **124**, 136
hier_flush, 120, **127**
hier_getKids, 119, **125**, 134
hier_getNames, 119, **125**, 133, 134
hier_getNodeId, 120, **126**, 134, 140
hier_getParent, 119, **125**, 134
hier_getPath, 120, **126**, 135–138
hier_getRoots, 119, **124, 125**, 133
hier_init, 117, 119, 122, **123**, 133, 134, 137, 140
hier_insert, 120, **126**
hier_lastId, 119, **124**, 136
hier_quit, 119, 122, **124**
hier_remove, 120, **127**
hier_search, 119, **125**, 135, 136
hier_setCosts, 120, **126**
query_distance, 121, **129**
query_findSource, 121, **130**, 137
query_nn, 121, **129**, 137
query_range, 121, **129**, 138
tcp_echo, 119, **123**
tcp_exit, 119, **123**
thes_getCategories, 120, **127**, 135
thes_getSynonyms, 120, **128**, 136
thes_init, 117, 120, 122, **127**, 135, 137
thes_quit, 120, 122, **127**
decision making
agent, 17
decision policy, *see* policy, decision 22
decision problem, 400, **400**, 401–403, 405, 407, 460
degrees of cooperation, **346**
Del, **143**
delayed action, *see* action, delayed 14
deontic closure, *see* closure, deontic 174
deontic consistency, *see* consistency, deontic 173
for map, 231
of $\mathcal{PS}$, **309**
dependency
causal, **357**
derivation
resolvent, **375**
d_G, **60**
DISCO, 106
distance
(between nodes), **42**
function, 42, 49
distance function, 58, 61
composite, 58, **58**, 59, 61
distortion
action secure, 344
contact, 341
correct, **346**
data, 341
data secure, 344, 347
degree of, 345
function, *see* function, distortion 338
maximally cooperative, 338, **347**, 391
policy, 340, 341, 343, 346, 366, 390
action secure, **344**
secure, 347
secure, **344**, 345
security-preserving, 338
service, 338, 397
statically secure, 390
Distributed Problem Solving, 52
distribution
probability, **297**

E
efficiently computable, 399
execution
  weakly concurrent, 410
expressiveness, 222
EXPTIME, **401**
EXPSPACE, **401**
$\mathcal{S}^{\text{ext}}$, 242, 244, 246, 247
extended code calls, **229**

F
$\mathcal{F}$, **76**
fact correspondence relation, *see* relation, fact correspondence 352
fact language, **333**, 335, 351, 372
  approximate, *see* approximate, fact language 352
feasibility
  local, 247
feasible belief status set, *see* status set, belief, feasible 238
feasible execution triple, **146**, 147, 148, 150–152, 154
feasible probabilistic status set, *see* status set, probabilistic, feasible 311
feasible status set, *see* status set, feasible 175
find_nn, 60, 69, 121
  algorithm, **64**
  ANSTABLE, 61, 64
  next_nbr, 61, 64
  num_ans, 61
  relax_thesaurus, 62
  search_service_table, 61, 64
  Todo, 61, 64
finite state automaton, *see* automaton, finite state 19
finiteness, **465**
finiteness property
  downward, 466
finiteness table, 463–465, **465**, 475, 476, 495, 506, 507
fragments, 23
FSAT, 405
function
  agent action security, **339**
  agent secrets, **339**
  approximate state, *see* approximate, state function 354
  distortion, 338, 364, 396
  service distortion, **340**
  service request evaluation, **337**, 338

G
$\Gamma^{[]}(a)$, **229**
Garlic, 105, 106
graph
  weighted directly acyclic, **41**
grounded, 241
groundedness
  of a probabilistic status set, **311**
  rational status set, **178**
  wrt $\mathcal{BS}$, **241**

H
$\mathsf{h_part}(\chi)$, **223**
hard, **402**
hardness, **402**, **405**
Head-CFT, **470**
heterogeneous data, *see* data, heterogenous 15
history, 332, **334**, 335, 340–344, 347, 350, 351, 359, 363, 366, 369, 371, 373, 374
  approximate, 354, 358, 361, 369, 372, 377
  approximate current, **351**
  approximation language, 373
  approximation rule, **372**, 374, 376, 382
  code call condition, *see* code call condition, history 374
  compatible, **342**
  component, 369, **369**, 370, 382
  condition, **370**, 379, 382, 384, 385, 390
  constraint, *see* constraint, history 373
  constraint language, **373**
  correspondence relation, **351**
  package, 371
  possible, **335**
  update actions, 371

I
identity, 303
IDL, **110**
IDL*IDL*, **114**
ignorance, 303
IMPACT server, **117**
  architecture, **117**
  handle, **117**
induced status set, **227**
$\mathsf{Info}(\cdot)$, **229**
$\mathsf{Info}(a)$, *see* $\Gamma^{[]}(a)$ 229
$\mathsf{Info}(\cdot)$, 230
InfoSleuth, 105
InfoSleuth, 107
input item atom, *see* item atom, input 55
inputs
  service description, 53, 55
integrity constraint, *see* constraint, integrity 142
intentions, 17
`isagent`, 3, 29
item, **54**
  annotation, **304**

item atom
  input, 55, **55**
  output, 55, **55**
item list, *see* list, item 55

J
Java agent, **146**

K
KIF, 21, 74

L
languages
  logical, 16
layering
  canonical, 477, 478, **478**, 496, 497
layering function, **472**
layers
  of an agent program, **473**
list
  item, **55**
literals
  action status
    conflicting, **468**
local
  coherence, **236**
  feasibility, **231**
logical languages, *see* languages, logical 16

M
M3SAT, 152, 154, 402, 420–422, 427, 431, 433, 437, 440, 446–449
map, **225**
MapObject, 13
mar, **225**
maximally cooperative distortions, *see* distortion, maximally cooperative 347
maximum clique, 406
MAXP, 451, 458
mechanisms
  bidding, 18
  negotiating, 18
mediators, 20
message events, 333
message manager, 31
meta agent program, 209, 212, 224, 225
meta agent rule, **225**
metaknowledge, 32, 34–36
metric, **49**, **58**
MIND, 105
modality ordering, **474**
mode realizability, 516
monotonicity, 303
Multi-Agent systems, 52
MULTIBASE, 105

N
name, **143**
  service description, 31, 39, 53
NASA hierarchy, 68, 69
net
  contract, **288**, 290
"No"-instance, **401**
no-go areas, 35, 57
noun-term, 38, **39**, 59
nounID, **46**
Nouns, **39**

O
ODBC, 16
OLE, 115
ontologies, 72
optimization problem, 405–407, 415, 425, 430, 431, 448, 451
OQL, 16
ORB, 110, 113–115
OTM, 403
output item atom, *see* item atom, output 55
outputs
  service description, 53
overestimations
  correct, **357**

P
$\wp$
  (as a graph mapping), **41**
permutation equivalence
  renaming, 491
$\Pi_{\mathsf{b}}^{\text{action}}(\mathcal{BS})$, **227**
$\Pi_{\sigma}^{\text{action}}(\mathcal{BS})$, **227**
$\Pi_{\mathsf{b}}^{\text{state}}(\mathcal{BS})$, **227**
$\Pi_{\sigma}^{\text{state}}(\mathcal{BS})$, **227**
plant, *see* agent, plant 14
policy
  decision, 22
polynomial hierarchy, 403–405, 414, 426, 444, 455, 457, 458
polynomial-time computable, 399, 400, 403, 406, 410, 416, 421, 423, 424, 427, 432, 436, 446, 452, 458
possible history, *see* history, possible 335
possible history approximation, *see* approximation, possible history 350
Pre, **143**
Precondition-CFT, **471**
preference, **191**
  strong, 192
  weak, **192**

prefixpoint, 314
proactive systems, *see* systems, proactive 6
probabilistic agent program, *see* agent program, probabilistic 304
probabilistic code call
  coherent, **300**
probabilistic code call atom, **301**
probabilistic code call condition, **301**
probabilistic conjunction strategy $\otimes$, **302**
probabilistic state consistency, *see* state consistency, probabilistic 310
probabilistic status set, *see* status set, probabilistic 306
problem reduction, **402**
program
  agent, *see* agent program 161
  meta agent, 209, 212, 224, 225
program closure
  of $\mathcal{BS}$, **235**
BT$^{\mathbf{a}}$: proj-select(agent, $=$, $\mathfrak{h}$), **221**
PSPACE, 402–404
pure history constraint, *see* constraint, pure history 373

Q
QBF, 403, 404, 407, 427, 433, 440, 445, 452, 454–456

R
random variable, **297**, 299–301, 320, 321
range, **66**
  algorithm, **66**
range, 66, 69, 121
  expand, 66
  RelaxList, 67
  Todo, 66
range computation, 66
range retrieval, **49**
rational probabilistic status set, *see* status set, probabilistic, rational 311
reactive systems, *see* systems, reactive 6
reasonable probabilistic status set, *see* status set, probabilistic, reasonable 312
reasonable status set, *see* status set, reasonable 184
recognition problem, 409, 411
Recognition Problem, 412, 413
recognition problem, 414, 415, 420, 422, 425, 428, 431, 433, 436, 445, 448, 450, 452, 455, 457, 458
$\mathsf{red}^{\mathcal{BS}}(\mathcal{BP}, \mathcal{O}_{\mathcal{S}})$, **242**
regularity, 475, 480, 484, 493
relation
  agent consequence, **335**
  approximate consequence, *see* approximate, consequence relation 356
  condition correspondence, **353**
  fact correspondence, **352**, 356
  history correspondence, *see* history, correspondence relation 351
resolvent derivation, *see* derivation, resolvent 375
RETZINA, 52
$[\rho]$, **227**
rule
  action, 160
rules
  conflicting, **468**

S
$\mathcal{S}$, **76**
safety
  strong, **466**, 467, 472, 475, 477, 498, 507
SAT, 402, 405, 407
satisfaction
  action constraint, **158**
satisfaction of an annotated ccc, *see* annotated ccc, satisfaction of an 307
schema, **143**
search problem transformation, **405**
secrets
  approximate, *see* approximate, secrets 356
  violated, 358
secrets approximation rule, *see* approximation, rule, secrets 372
secure distortion, *see* distortion, secure 344
security, 23, 33, 46, 531
  data, 330, 331, 343, **343**, 349, 358, 361, 364, 366, 368, 385, 394, 395, 397
    approximate, 331, 359, **359**, 360, 368
    static, **364**
  surface, 330, **341**, 343, 366, 368
Sem_{feas}, 219
Sem_{rat}, 219
Sem_{reas}, 219
semantic equivalence, 41
sequence, 221, 227, **227**, 228, 229, 231, 245, 247
server, 29, 37, 46
  registration, 37–39, 45
  synchronization module, **49**
  thesaurus, 37, 47, 62
  type, 37
  yellow pages, 37, 48, 53, 57, 63, 68
service description, 31, 53, **55**, 56
  inputs
    discretionary, 31
    mandatory, 31
  outputs, 31
service description attributes, *see* attributes, service description 53

service description inputs, *see* inputs, service description 53
service description name, *see* name, service description 53
service description outputs, *see* outputs, service description 53
service distortion function, *see* function, service distortion 340
service name, **39**
service request evaluation function, *see* function, service request evaluation 337
service rules, 338
Service Table, 67
services, 39
  dictionary, 15
  matchmaking, 21, 38, 58, 59, 68
    nearest neighbor, **48**, **60**
    range, 49, 66
  ontological, 15
  registration, 15
  security, 15
  thesauri, 15
  yellow pages, 3, 14, 15, 21, 37
ServiceTable, 45, 61, 69, **122**
SHADE, 21, 74
σ
  as a sequence, **227**
Σ-Hierarchy, **41**, 62
Σ-node, 41
node
  Σ, 41
similar matches, 68, 74
SMART algorithm, 21, 74
software agent, 1
software infrastructure, 3
SQL, 16
state
  of an agent, **79**, 89, 92, 93
state approximation rules, *see* approximation, rule, state 372
state consistency
  probabilistic, **310**
state-independent, 196
static agent approximation, *see* approximation, agent, static 364
static data security, *see* security, data, static 364
status set, **172**, 174, 175
  belief, *see* belief status set 226, **226**
    feasible, **238**
  feasible, 171, 172, 175
  induced, *see* induced status set 227
  optimal *Sem*, 196
  probabilistic, 306, **306**, 308–317, 319, 322
    feasible, **311**
    rational, **311**, 314, 315, 319
    resonable, **312**
  rational, 178, 182, 200, 407, 414, 415, 417–421, 423–429, 431, 433, 435–437, 439, 441, 443–446, 452, 456–458
    A-, 447, 451
    $A(S)$-, 452, 453
    F-preferred, 436–439, 455–459
    F-preferred , 437
    weak, 186, 188, 414, 419–421, 430–436, 446–455, 458
    wrt $\mathcal{BS}$, **241**
  reasonable, 171, 184, 201
    weak, 188
    wrt $\mathcal{BS}$, **242**
  relativized, 188
status sets
  probabilistic
    feasible, 312
strongly safe, 467, **467**, 472, 477, 493, 494, 496, 498, 503
  as an IC, **476**
surface security, *see* security, surface 341
synchronization module, **49**
systems
  proactive, 6
  reactive, 6

T
$\mathcal{T}$, **76**
$\mathbf{T}_{\mathcal{PP},\mathcal{O}_S}$, **314, 315**
TCP/IP, **117**, 122
temporal reasoning, 32
$\mathbf{TPA}_{\mathcal{P},\mathcal{O}_S}$, 189
$\mathbf{T}_{\mathcal{P},\mathcal{O}_S}$, 190, 191
tractability, 400
$\mathfrak{Trans}^{\text{action}}(\mathcal{BS}, \text{b})$, **245**
$\mathfrak{Trans}$, 244, **244**, 245, 249
  inductive definition, 243
$\mathfrak{Trans}(\mathcal{BP})$, 245, 248, 249
$\mathfrak{Trans}^{\text{state}}(\mathcal{BS}, \text{b})$, **245**
transducer, 20, **405**
Turing machine
  deterministic, **401**, 406
  nondeterministic, **401**, 402, 403
  oracle, **403**
type hierarchy, 54, **54**
type variable, 54, **54**

U
uncertainty, 11, 13, 32
  about beliefs, 296
  about beliefs about others actions, 296

uncertainty (*contd.*)
about effects, 295
about state, 295
positional, 295
underestimation
correct, **357**
US ARMY, 209

V
verbID, **46**
Verbs, **39**
violated secrets, **342**, 343, *see* secrets, violated 358, 361
vocabulary, 41

W
Wintertree Software, *see ThesDB* 47
wrapper, 20, 29

Y
yellow pages, 48
"Yes"-instance, 154, 401, **401**, 448, 452